



VOLTAGES ARE MEASURED ON A METER OF 20,000 Ω/VOLT, WITH NO AERIAL CONNECTED  
 RESISTOR VALUES ARE IN OHMS  
 CAPACITOR VALUES ARE IN MICRO-MICROFARADS EXCEPT WHERE OTHERWISE SHOWN  
 CHOKE VALUES ARE IN MICRO-HENRIES  
 T2, T3, T4 AND L5 ARE TUNED TO 12.5 Mc/s  
 L8 AND T6 ARE TUNED TO 19 Kc/s, T7 IS TUNED TO 38 Kc/s AND L9 IS TUNED TO 67 Kc/s

\* C50 IS 3000pF ON EUROPEAN MODEL  
 C59 AND C60 ARE 2000 pF ON EUROPEAN MODEL  
 C50 IS 4000pF ON U.S. MODEL  
 C59 AND C60 ARE 3000pF ON U.S. MODEL

ALL COMPONENTS INSIDE THESE DOTTED LINES ARE CONTAINED IN THE  
 DECODER UNIT FITTED INSIDE THE TROUGHLINE TUNER  
 THE CONNECTIONS TO THE DECODER ARE MADE VIA A SIX CONTACT  
 PLUG AND SOCKET AND THE CONTACTS ARE NUMBERED VERTICALLY  
 FROM THE BOTTOM

CIRCUIT DIAGRAM

SEAVING